



Base Model—Crank Hand Pump

- Economic Manual Hand Crank Pump
- Inexpensive, includes bung adapter, easy to install
- Recommended for Drum Usage
- Ideal for low volume needs



Entry Level—JuniorFlux

- Economic Electric Motor
- Ergonomic Handle
- Economic Plastic Dispensing Nozzle
- 8 Feet of PVC Hose
- Up to 5 gallons per minute
- Includes Bung Adapter
- Durable, Reliable and Easy to Clean
- One-Year Warranty
- Recommended for Drum Usage
- Recommended for low volume needs



Premium—Flux Industrial

- Heavy Duty Industrial Variable Speed Motor
- 10 Feet Industrial Grade EPDM Hose
- Stainless Steel Automatic Shut-off Nozzle
- Flow Rates up to 10 gallons per minute
- Includes Bung Adapter
- One -Year Warranty
- Recommended for Drum Usage
- Ideal for low to moderate volume needs

For More Information Call Your Sales Rep





PIUSI—Suzzara Blue

- True “Closed System”
- 110v Stainless Steel, Self-priming Electric Motor
- Side Mounted Bracket
- Stainless Steel Automatic Shut-off Nozzle
- Flow Rates up to 10 gallons per minute
- In-Line Flow Meter
- Recommended for IBC/Tote Usage
- Ideal for “Closed System” Applications, providing the highest level of contamination protection
- Compatible with the Micro Matic EPV System
- Ideal for moderate to heavy applications

Insulated Tote Cabinet



- Weather Proof—protects pump, tote and equipment during inclement weather
- Light Weight & Insulated—walls, doors and roof made of insulated foam panels (R-7 rating)
- Vented—prevents condensation buildup and vacuum pressure when opening door
- Pre-Wired—light, on/off switch & receptacle meets NFPA & NEC requirements
- Heavy-Duty, Locking Doors—tote and dispense doors can be locked for additional security
- Stainless Steel Hardware—all latches, hinges and locks will not rust or corrode
- Reinforced Chassis—Two-way forklift compatible frame will accommodate up to 350-gallon tote
- Bolt Down Design—protects against strong winds and seismic code requirements
- Protective Kick Plate—prevents forklift damage to back panel when transferring totes
- Dispense Door—small door for driver use will prevent loss of heat
- Decal Package & Driver Instructions
- Available in Three Footprint Designs—standard, narrow (for fuel island applications) and double-wide

OPTIONAL EQUIPMENT

Heater and/or A/C Unit with Thermostat

Automatic on/off light switch

Hose Reel

	Size
Insulated Tote Cabinet	Single
	Single Narrow
	Double
	Double Narrow

For More Information Call Your Sales Rep



Commercial DEF System



Retail DEF System



Mini Bulk Storage Systems

- Environmentally safe
- Secondary containment
- Proven, reliable state-of-the-art design and technology
- All systems meet and exceed ISO 22241 standards for storage and dispensing of AUS-32
- Compatible with all major dispensers, card readers and POS systems
- Pre-wired with electronic control panel for easy turn-key installation
- Insulated housing for hot or cold weather climates
- Bottom fill-port with SS Dry Connect, overfill protection, and inventory level display
- Available in one or two hose configurations
- Heavy duty poly tank with capacity from 725 gal to 4,000 gal

OPTIONS INCLUDE

Remote monitoring system

Thermostatically controlled heater

	Size
Retail DEF System	800 gal
	1000 gal
	2000 gal
Commercial DEF System	800 gal
	1000 gal
	2000 gal

For More Information Call Your Sales Rep

